

# FLEET XP 40

High speed diesel engine oil

## Description

**Fleet XP 40** is specifically designed for high speed diesel engines. It is formulated from high quality base stock and additives detergent-dispersant, antioxidant, antiwear and antifoam properties.

## Applications

**Fleet XP 40** is recommended for lubrication of high speed diesel engines such as fleet, bus, micro bus, stationary machinery, marine including supercharged applications.

## Specification Meets

**Fleet XP 40** meets the requirement of API service CF level.

## Advantages

- ▶ Good thermal and oxidation stability
- ▶ Excellent detergency and dispersancy properties
- ▶ Elimination sludge, varnish & carbon deposits
- ▶ Excellent antiwear and anticorrosion properties
- ▶ Excellent antioxidant, antirust, and antifoaming properties
- ▶ Good rust and corrosion protection

## Typical Data of FLEET XP 40

Characteristics	Unit	FLEET XP 40	Test Method
Color		L 2.5	ASTM D 1500
Density @ 15 °C	kg/L	0.8931	ASTM D 4052
Kinematic Viscosity @ 40 °C	cSt	150.78	ASTM D 445
Kinematic Viscosity @ 100 °C		15.25	
Viscosity Index		102	ASTM D 2270
Flash Point (COC)	°C	250	ASTM D 92
Pour Point	°C	-15	ASTM D 97
Total Base Number	mg KOH/g	10.5	ASTM D 2896

\* the typical characteristic mentioned represent mean values